

PLASTABRICK MESHING RENDER FINES



PBMRF is a factory mixed adhesive render suitable for use as a jointing compound on 7.5mm fibre-cement sheets. PBMRF can be universally applied to outdoor areas and has excellent properties while maintaining optimum flexibility to allow for movement in the structure of the wall.

**Application:**

PBMRF should be drill mixed only and can be used to a maximum thickness of 5mm in one coat. The use of 70mm wide fibreglass mesh embedded wet-in-wet in the plaster is essential. All sheet joints must be meshed in this way. Plastabrick recommends the use of Fibreglass reinforcing mesh.

**Coverage:**

A 25 kg bag of PBMRF will normally be sufficient to cover joints on approximately 90 square metres of wall.

**Important:**

Do not under any circumstances add foreign substances other than clean water to premixed mineral plasters.

Do not add further water to PBMRF/water mixture later than two hours after original mixing time.

**Storage:**

PBMRF is packaged in 25kg paper bags, with 40 bags (1 tonne) per pallet.

PBMRF can be stored in a dry place for up to six months.

**Quality Control:**

PBMRF is quality controlled at the point of manufacture and tested by independent Laboratories.

**Service:**

At the forefront of plastering technology, Plastabrick NZ Ltd offers its assistance and experience in the selection and use of our products.